

WEESS WALLBOX

Home Charger
www.weess.com

WEESS GmbH
Graf-Adolf-Straße 14, 40212 Düsseldorf
Tel: +49-211-6509-7777
Email: info-eu@weess.com



Smart Version of AC Charger

DATA SHEET (EN)

* WALLBOX DATASHEET

Performance Specifications

AC Power Supply	WEESS-A007xxx	1P+N+PE
	WEESS-A011xxx, WEESS-A022xxx	3P+N+PE
AC Power Supply	WEESS-A007xxx	7.4kw
	WEESS-A011xxx	11kw
	WEESS-A022xxx	22kw
Rated Voltage	WEESS-A007xxx	AC 230V, 50/60Hz
	WEESS-A011xxx, WEESS-A022xxx	AC 400V, 50/60Hz
Rated Current	WEESS-A011xxx	16A
	EAW-A007xxx, EAW-A022xxx	32A

Sockets/ Plugs	WEESS-A0xxSxx	Socket, Case B connection
	WEESS-AOxxTxx	Cable(5m), Case C connection
Charge Mode	Type2 IEC 62196-2	

Charging Control	Smart phone App control, Tap card control, Plug-and-charge	
Display Screen	WEESS-A0xx1x	3.8-inch LCD screen
Indicator Light	WEESS-AOxxx0x	4 LED lights
Communication Interface	WiFi/BT, 4G, LAN	
Communication Protocol	OCPP 1.6J	

RCD	Type A+DC6mA(TUV RCD+RCCB)	
Altitude	2000m	
IP Code	IP55	
Storage temperature	-40~75°C	
Operation temperature	-30-50°C	
Relative humidity	95%RH, No water droplet condensation	
Vibration	0.5G. No acute vibration and impaction	
Safety Protection	Over current protection, over voltage protection, under voltageprotection, over temperature protection, leakage protection,unconnected PE ground protector etc	

Installation location	Indoor or outdoor, good ventilation, no flammable, explosive gases	
Product Weight (Nw)	WEESS-A022Sxx	2.6kg
	WEESS-A011Sxx	2.4kg
	WEESS-A007Sxx	2.4kg
	WEESS-A022Txx	5kg
	WEESS-A011Txx	3.8kg
	WEESS-A007Txx	4kg
Product Size	WEESS-A0xxSxx	388.45mm*202.45mm*116mm(H*W*D)
	WEESS-AOxxTxx	388.45mm*202.45mm*107.26mm(H*W*D)
Packaging Box Dimensions	WEESS-A0xxSxx	455mm*260mm*150mm(H*W*D)
	WEESS-AOxxTxx	455mm*260mm*230mm(H*W*D)
Mounting	Wall-mounted or pole-mounted (mounting pole is optional)	